

SYMPTOM	POSSIBLE ISSUES OR COMMENTS	SOLUTIONS
CPR MONITOR		
CPR Monitor lights are not working properly To help understand how the CPR Monitor works, please note that the CPR Monitor lights are powered by a small current generated by the CPR Monitor Please follow the troubleshooting tips at right in the order they are listed for best results	 Chest compressions are not deep enough to signal CPR Monitor Batteries are not installed, need replacing or are not inserted correctly in the CPR Monitor CPR Monitor may be clogged with plastic dust, interrupting the signal to the Monitor CPR Monitor needs to be replaced 	 Compress the chest until the beep is audible from the CPR Monitor at 2"-2.4" Install or replace batteries into CPR Monitor (back of manikin, left shoulder area) - requires 2-AA (1.5V) batteries Remove CPR Monitor and blow out dust – then replace CPR Monitor and reconnect Exchange CPR Monitor with working manikins (if available) to determine if CPR Monitor needs to be replaced
CPR Monitor lights are all on	Batteries are running low	Replace batteries
CPR Monitor red light is blinking	This is normal after replacing batteries, manikin is paused or is connecting to CPR Feedback app - may blink up to 10 minutes to indicate ready status	Commence or resume compressions - blinking will stop and feedback rate signals will begin
MANIKIN TORSO AND FAC	CE-SHIELD/LUNG-BAG	
Cannot hear a beep when doing compressions	 Hand position and/or compression angle may be incorrect Compressions may not be deep enough to activate the CPR Monitor CPR Monitor may be broken Batteries may be dead or misassembled 	 Confirm correct hand placement and compress straight down from directly above the manikin Compress between 2 and 2.4 inches depth Replace batteries



SYMPTOM	POSSIBLE ISSUES OR COMMENTS	SOLUTIONS		
MANIKIN TORSO AND FACE-SHIELD/LUNG-BAG (continued)				
Chest will not rise when breaths are given	 Head is not tilted back enough to open airway Face Shield is not attached Lung Bag may be damaged or torn (Note: there are holes in the Adult Lung Bag necks by design to allow deflation) Lung Bag is not lying flat or properly positioned over the compression plate and/or neck of bag is twisted Lung Bag has accumulated moisture in the neck, which may cause the sides to stick together and prevent air passage Neck of Lung Bag twisted Excessive residual moisture in Lung Bag Breath Sensor not connected to Lung Bag properly 	 Push on forehead and/or lift at chin to tilt head back enough to open airway Attach Face Shield at "buttons" on the side of the manikin's head below ears Blow into the Face-Shield/Lung-Bag while it is outside the manikin to make sure it inflates properly – if not, discard and use another Face-Shield/Lung-Bag Revisit instructions for installing a Face- Shield/Lung-Bag earlier in this manual A new Face-Shield/Lung-Bag should be installed after each class, or more often if needed due to excessive moisture buildup Remove Lung bag and reinstall in accordance with the Face-Shield / Ventilation Lung-Bag instructions Replace lung bag, see Face-Shield / Ventilation Lung-Bag instructions 		
Manikin torso will not stay closed Manikin torso opens when breaths are given	 Tabbed latches at shoulders may not be securely closed Chest frame may be stretched from improper opening of torso Tabbed latches at shoulders are broken from improper opening of torso 	 Close tabs at shoulders – a snap will be heard when shoulder tabs are properly latched Open torso and attempt to reverse stretched out frame by pushing it in the opposite direction Torso Frame needs to be replaced (RPP-AFRAME-1)* 		



SYMPTOM	POSSIBLE ISSUES OR COMMENTS	SOLUTIONS
MANIKIN TORSO AND FA	CE-SHIELD/LUNG-BAG (continued)	
Rattling in chest	Piston Plug may be loose inside manikin	Remove CPR Monitor Assembly, reposition Piston Plug and reinstall CPR Monitor per Series 2000 Add-On Kit Installation Guide
Chest Plate is broken	Typically results from a combination of incorrect (not centered) hand placement, compression angle not straight down from directly above and/or overzealous compression force	 Replace sleeve in chest with part RPP- APLATE-1 (compression assembly includes chest plate, screw and sleeve)*
PRESTAN CPR BLUETOO	TH ENABLED APP	
"Unable to download app" error from App Store on iOS device	 No/Poor Wi-Fi signal Not enough storage on smart device App Store malfunctioning Smart device malfunctioning Smart Device needs updated Setting on Smart Device blocking download/purchase 	 Check Wi-Fi Connection If unable to get Wi-Fi, make sure the device has a strong mobile data connection Check Wi-Fi Connection Check Storage Space in your iPhone Restart App Store Restart iPhone Update iOS Pause and restart app download Disable Restrictions for Installing Apps Allow App Store purchases in Content & Privacy Restrictions



SYMPTOM	POSSIBLE ISSUES OR COMMENTS	SOLUTIONS		
PRESTAN CPR BLUETOOTH ENABLED APP (continued)				
Unable to download app from Google Play Store on Android device	 No/Poor Wi-Fi signal Not enough storage on smart device App Store malfunctioning Smart device malfunctioning Smart Device needs updated Setting on Smart Device blocking download/purchase 	 Check Wi-Fi Connection If unable to get Wi-Fi, make sure the device has a strong mobile data connection Clear the cache & data of the Play Store Restart Android Device Check Storage Space in your Android Device Check your SD card if your device has one. Try ejecting and reinserting card. 		
Manikin won't connect to smart device	 Smart device battery and/or CPR Monitor battery may be low Bluetooth (BT) is not enabled or not available on smart device Smart device too far from manikin Smart device not compatible Smart device / CPR Monitor needs reset or restarted Smart device not finding CPR Monitor signal 	 Change batteries in manikin Make sure BT is enabled on your Smart Device and you can see the BT symbol at the top of the screen; If you do not see the symbol, go into the settings on your device and enable BT Make sure manikin is within operating distance of approximately 20 feet from the smart device. During the connection process you may need to have the devices within 5 feet for easier connection Ensure your device is running the latest version of its operating system. For Apple devices: Compatible with iPhone, iPad and iPod touch. Requires iOS or iPadOS 13.0 or newer. For Android devices: Requires Bluetooth® LE or 5.0 enable device running Android 5.0 or newer. 		



SYMPTOM	POSSIBLE ISSUES OR COMMENTS	SOLUTIONS	
PRESTAN CPR BLUETOOTH ENABLED APP (continued)			
Manikin won't connect to smart device		Attempt soft restart of devices:	
(continued)		Manikin - remove batteries and reinstall	
		Smart Device - put device into and out of Airplane mode	
		 Remove some older BT connections that you no longer use on your device by unpairing: 	
		iOS settings - remove a device by tapping on its name and then tap "Forget this Device"	
		Android settings - remove a device by tapping on device name, then tap "Unpair"	
		After removing a device start again to rediscover the device when needed	
		Make sure your smart device is charged and not in low power mode.	
		You may need to rediscover a device to get it to start working again:	
		iOS settings - Remove a device by tapping on name and then tap "Forget this Device".	
		Android settings - Remove a device by tapping on device name, then tap "Unpair".	
		After removing a device start again to rediscover the device when needed.	

^{*} Contact your PRESTAN Authorized Distributor to either purchase the replacement part or receive it at no charge if the manikin is within PRESTAN's warranty period and is a qualifying warranty repair.